

**Edwards & Angell** LLP

101 Federal Street Boston, MA 02110 617.439.4444 fax 617.439.4170  
www.EdwardsAngell.com

Date : May 10, 2005

Pages (including cover) : <sup>7</sup>5**Sender :**

---

Name	William J. Daley, Jr.	Phone	617-439-4444
Fax	617-439-4170		
Email	wdaley@EdwardsAngell.com		

---

**To :**

Name	Company	Fax	Phone
Vincent Kovalick Art Unit 2673	USPTO	571-273-7769 7669	

If you experience problems receiving this fax, please call Safiya Jarvis at 617-439-4444.

**Message :**

U.S.S.N.: 09/851,885

Inventors: Kubota, et al.

Entitled: DATA SIGNAL LINE DRIVE CIRCUIT, IMAGE DISPLAY DEVICE  
INCORPORATING THE SAME, AND ELECTRONIC APPARATUS USING THE SAME

Group: 2673

Examiner: Kovalick, Vincent E.

Our Reference: 55845 (70904)

Resend with claims 11, 12, 13  
added

**Fax**

**Confidentiality Note :** The documents accompanying this facsimile contain information from the law firm of Edwards & Angell LLP, which may be confidential and/or privileged. The information is intended only for the use of the individual or entity named on this transmission sheet. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or the taking of any action in reliance on the contents of this facsimile is strictly prohibited, and that the documents should be returned to this firm immediately. If you have received this facsimile in error, please notify us by telephone immediately so that we can arrange for the return of the original documents to us at no cost to you.

**Annotated version**

2. (Currently Amended) The image display device as defined in claim 1, wherein:  
~~claims 1 or 122;~~  
~~-----wherein:~~

only one of the parts and entireties of the drive circuit(s) operates at any given time.

3. (Currently Amended) The image display device as defined in claim 1, wherein:  
~~claims 1 or 122;~~  
~~-----wherein:~~

the same part(s) and entirety(ies) of the drive circuit(s) is(arc) driven throughout one or more frame periods.

4. (Currently Amended) The image display device as defined in claim 1, wherein:~~claim 1 or 122;~~  
~~-----wherein:~~

two or more of the parts and entireties of the drive circuit(s) are switchably driven in one frame period.

5. (Currently Amended) The image display device as defined in claim 1, wherein:  
~~claims 1 or 122;~~  
~~-----wherein:~~

at least two of the parts and entireties of the drive circuit(s) write image data in respective areas on a screen.

6. (Currently Amended) The image display device as defined in claim 1, wherein:  
~~claims 1 or 122;~~  
~~-----wherein:~~

a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least two of the parts and entireties of the data signal line drive circuit write image data in one partial or whole area on a screen in one frame period.

11. (Currently Amended) The image display device as defined in claim 1, wherein:  
~~claims 1 or 122,~~

~~wherein:~~

a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least one of the parts and entireties of the data signal line drive circuit writes image data in a blanking period of each horizontal scan period.

12. (Currently Amended) The image display device as defined in claim 1, wherein:  
~~claims 1 or 122,~~

~~wherein:~~

a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least one of the parts and entireties of the data signal line drive circuit writes image data with a predetermined delay from another part or entirety of the data signal line drive circuit.

13. (Currently Amended) The image display device as defined in claim 1, wherein:  
~~claims 1 or 122,~~

~~wherein:~~

the parts and entireties of the drive circuit(s) are located opposing one another across the pixel array.

126. (New) The image display device as defined in claim 122, wherein:

only one of the parts and entireties of the drive circuit(s) operates at any given time.

127. (New) The image display device as defined in claim 122, wherein:

the same part(s) and entirety(ies) of the drive circuit(s) is(are) driven throughout one or more frame periods.

128. (New) The image display device as defined in claim 122, wherein:

two or more of the parts and entireties of the drive circuit(s) are switchably driven in one frame period.

129. (New) The image display device as defined in claim 122, wherein:  
at least two of the parts and entireties of the drive circuit(s) write image data in respective areas on a screen.

130. (New) The image display device as defined in claim 122, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least two of the parts and entireties of the data signal line drive circuit write image data in one partial or whole area on a screen in one frame period.

131. (New) The image display device as defined in claim 122, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least one of the parts and entireties of the data signal line drive circuit writes image data in a blanking period of each horizontal scan period.

132. (New) The image display device as defined in claim 122, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least one of the parts and entireties of the data signal line drive circuit writes image data with a predetermined delay from another part or entirety of the data signal line drive circuit.

133. (New) The image display device as defined in claim 122, wherein:  
the parts and entireties of the drive circuit(s) are located opposing one another across the pixel array.

**Clean Version**

2. The image display device as defined in claim 1, wherein:  
only one of the parts and entireties of the drive circuit(s) operates at any given time.
3. The image display device as defined in claim 1, wherein:  
the same part(s) and entirety(ies) of the drive circuit(s) is(are) driven throughout one or more frame periods.
4. The image display device as defined in claim 1, wherein:  
two or more of the parts and entireties of the drive circuit(s) are switchably driven in one frame period.
5. The image display device as defined in claim 1, wherein:  
at least two of the parts and entireties of the drive circuit(s) write image data in respective areas on a screen.
6. The image display device as defined in claim 1, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least two of the parts and entireties of the data signal line drive circuit write image data in one partial or whole area on a screen in one frame period.
11. The image display device as defined in claim 1, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least one of the parts and entireties of the data signal line drive circuit writes image data in a blanking period of each horizontal scan period.
12. The image display device as defined in claim 1, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least one of the parts and entireties of the data signal line drive circuit writes image data with a predetermined delay from another part or entirety of the data signal line drive circuit.

13. The image display device as defined in claim 1, wherein:  
the parts and entireties of the drive circuit(s) are located opposing one another across the pixel array.

126. The image display device as defined in claim 122, wherein:  
only one of the parts and entireties of the drive circuit(s) operates at any given time.

127. The image display device as defined in claim 122, wherein:  
the same part(s) and entirety(ies) of the drive circuit(s) is(are) driven throughout one or more frame periods.

128. The image display device as defined in claim 122, wherein:  
two or more of the parts and entireties of the drive circuit(s) are switchably driven in one frame period.

129. The image display device as defined in claim 122, wherein:  
at least two of the parts and entireties of the drive circuit(s) write image data in respective areas on a screen.

130. The image display device as defined in claim 122, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least two of the parts and entireties of the data signal line drive circuit write image data in one partial or whole area on a screen in one frame period.

131. The image display device as defined in claim 122, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and  
at least one of the parts and entireties of the data signal line drive circuit writes image data in a blanking period of each horizontal scan period.

132. The image display device as defined in claim 122, wherein:  
a part or entirety of the data signal line drive circuit is provided in plurality; and

at least one of the parts and entireties of the data signal line drive circuit writes image data with a predetermined delay from another part or entirety of the data signal line drive circuit.

133. The image display device as defined in claim 122, wherein:  
the parts and entireties of the drive circuit(s) are located opposing one another across the pixel array.